

## Lyno griebtuvas

# WIRE ROPE (STEEL)

Grip	Outside Diameter	Safe Load (lbs.)
<b>1604-10</b>	1/16" - 3/16" (1.59 mm - 4.76 mm)	<b>2,500 lbs.</b> (1,134 kg)
<b>1604-20L</b>	1/8" - 1/2" (3.18 mm - 12.70 mm)	<b>5,000 lbs.</b> (2,268 kg)
<b>1625-20</b>	5/16" - 3/4" (7.94 mm - 19.05 mm)	<b>8,000 lbs.</b> (3,629 kg)
<b>1625-20 7/8</b>	7/16" - 7/8" (11.11 mm - 22.23 mm)	<b>8,000 lbs.</b> (3,629 kg)
<b>1625-20 1</b>	1/2" - 1" (12.70 mm - 25.4 mm)	<b>8,000 lbs.</b> (3,629 kg)

## Haven's™ Grips “Pork Chop”

Haven's Grips are designed for use when a light, compact grip is desired where conductor deformation is not a factor.

Tel.+370 676 65626 , [bagra@bagra.lt](mailto:bagra@bagra.lt)

† Gripping pressure of the knurled jaw is applied to 1/4" (6.35 mm) cable area.

† All 1625 series have a swing latch to help hold cable in the jaw.



1625-20



1604-20



1604-20L

Cat. No.	Latch Model	Min. to Max. Cable Diameter inches (mm)	Jaw Length	Approx. Weight Each
<b>2,500 lbs. (1,134 kg) Maximum Safe Load</b>				
1604-10	NA	.06" - .25" (1.52 mm - 6.35 mm)	N/A	1 lb. (.45 kg)
<b>5,000 lbs. (2,268 kg) Maximum Safe Load</b>				
1604-20	1604-20L	.125" - .50" (3.18 mm - 12.70 mm)	N/A	2.08 lbs. (1.14 kg)
<b>8,000 lbs. (3,629 kg) Maximum Safe Load</b>				
1625-20		.28" - .75" (7.11 mm - 19.05 mm)		
1625-20 7/8	Latch Included	.38" - .88" (9.65 mm - 22.35 mm)	N/A	4 lbs. (1.81 kg)
1625-20 1		.50" - 1.00" (12.70 mm - 25.40 mm)		

All dimensions are in inches (millimeters).

[www.kleintools.com](http://www.kleintools.com)  
www.kleintools.com

WIRE ROPE STEEL STRAND